




### HR 580 INJECTOR



<b>DESCRIPTION</b>	HR 580 Injector
<b>FEATURES</b>	<p>80,000 lbs CONTINUOUS Pulling Capacity.          40,000 lbs CONTINUOUS Snubbing Capacity.          Integral gearbox with variable displacement motor providing smooth speed control – from inches per min to 150 ft per min.          Suitable for use with all CT sizes from 1 ½” to 3 ½”.          Capable of running all grades of CT including QT1200.          ‘Quick Connect’ Gripper system.          Smaller than similarly rated Injector Heads.          Single unit dual acting Electronic Load Cell.          Dual counter head assembly.</p>
<b>SAFETY</b>	<p>Fitted with Hydraulic Gin pole for attaching safety harness / inertia reel.          Fitted with work platforms          All work platforms / ladders have a non-slip surface.          3T Hydraulic Winch fitted to prevent the requirement of manual stabbing of tubing.</p>
<b>CERTIFICATION</b>	Designed and manufactured in accordance with the current DCR regulations Certified to allow the duty holder to demonstrate compliance with the requirements of SI 913.
<b>DIMENSIONS</b>	1,327mm (4’ 4”)(W) x 1,391mm (4’ 7”)(D) x 2,648 mm (8’ 8”)(H)
<b>WEIGHT</b>	Gross Weight : 4,565 kg (5,215 kg Incl. Gooseneck)