



6 5/8" 10M "EH" SINGLE SHEAR / SEAL BOP

DESCRIPTION	6 5/8" 10M "EH" Shear / Seal BOP
FEATURES	<p>7 1/16" 10M BX156 Studded top flange connection. 7 1/16" 10M BX156 Open bottom flange connection. Integral equalising valves. Well pressure isolated from hydraulic system. Hydraulic system rated for 3000psi. Easy maintenance, no special handling tools required. No welds, side port flanges are integral to BOP body. Indicator rods give a reliable indication of ram position. Manual locking stems are non-rising. Shear rams are designed to cut up to 3.50" tubing, leaving a clean end for circulating fluids or easy fishing. Blades are tubing size specific. Blades have the ability to cut tubing & cable.</p>
SAFETY	<p>Swivel lift system, comprising: 2 Tonne SWL Lifting sling set & 4 Tonne SWL spreader beam. Shear / seal has its own dedicated transport basket.</p>
CERTIFICATION	<p>Lifting slings & spreader beam certified to DNV 2.7-1 NACE MR-01-75 for H2S Service API 6A, 17th Edition Independent Review Certificate</p>
DIMENSIONS	2159mm (7' 1") (L) x 813mm (2' 8") (W) x 813mm (2' 8") (H)
WEIGHT DATA	1270 kg

