



### NORSOK ZONE II 6V-92TA ENGINE UNIT

<b>DESCRIPTION</b>	NORSOK, Zone II 6V-92TA Engine Unit.
<b>ENVIRONMENTAL</b>	Fully soundproofed to 80dB(A) and built to the highest standards and current legislation. Includes fully enclosed drip pans with drainage points.
<b>OPERATION/SERVICE</b>	Intended for general pumping operations in oilfield environment.
<b>ENGINE</b>	Detroit Diesel 6V-92TA, 490 BHP Gross, 360 HHP MAX
<b>FUEL CONSUMPTION</b>	100 litres per hour under full load.
<b>FUEL CAPACITY</b>	600 litres
<b>AUXILLIARY HYDS</b>	47 l/min @ 240 bar (12.4 usgpm @ 3,480 psi)
<b>CONTROL PANEL</b>	Engraved stainless steel control panel giving central / remote control and visual display of rates, pressures etc.
<b>SAFETY</b>	Built to the ATEX directive (Equipment and Protection systems Intended for Use in Potentially Explosive Atmospheres). Emergency stop, fuel stop, fail safe system. Platform control shut downs available pneumatic or electric. Compliant with NORSOK Z-015 Regulations. Fitted with gas detection / shutdown system / visual / audible alarms & automatic / manual foam deluge system. Pyroban Exhaust Gas Cooling System Fitted. ISO Twistlock Castings fitted for securing to trucks. Tie-down rings fitted for chaining to trucks / vessel or rig site.
<b>FEATURES</b>	Two piece unit, for ease of transport / lifting. Incorporates quick latch system with hydraulic clamping. Compatible with SPM600, SPM900 & SPM1800 Pumps
<b>CERTIFICATION</b>	Certified to allow the duty holder to demonstrate compliance with the requirements of SI 913. ATEX Compliant.
<b>DIMENSIONS</b>	Engine Skid 4571mm(L) x 2438mm(D) x 2820mm(H)
<b>WEIGHT DATA</b>	Engine Skid Gross Weight : 13,500 KG

