



ZONE II HYDRAULIC POWER PACK

DESCRIPTION	Zone II Hydraulic Power Pack
ENGINE	4 Cylinder IVECO diesel engine, 58 kw @ 2500 rpm (79 hp)
FEATURES	Stand alone power pack, to supply hydraulic power for various, oilfield equipment. Totally enclosed & sound proofed. Clearly laid out ergonomic anodized aluminum control panel All components easily accessible for maintenance Forklift pockets integrated into frame structure.
SAFETY	Fully enclosed in a lifting / transport frame. Enclosed pollution drip pans with drainage points. Thermally and acoustically insulated panels and doors Designed to comply with common industry standards and regulations.
CERTIFICATION	Designed and built to BS EN12079 CE Marked Certified to allow the duty holder to demonstrate compliance with the requirements of SI 913.
DIMENSIONS	2050mm (6' 9") L x 1200mm (4') W x 1420mm (4' 8") H
WEIGHT DATA	2,700 kg





SPEED / PRESSURE / FLOW

Large Pump

Engine Speed (rpm)	Hyd Pressure (psi)	Hyd Pressure (bar)	Hyd Flow (l/min)	Hyd Flow (usgpm)
2000	0	0	177	46.7
2000	500	34.5	173	45.7
2000	1000	69	172	45.4
2000	1500	103.5	169	44.6
1900	2000	138	159	42
1750	2500	172.5	145	38

Small Pump

Engine Speed (rpm)	Hyd Pressure (psi)	Hyd Pressure (bar)	Hyd Flow (l/min)	Hyd Flow (usgpm)
2000	0	0	34	9
2000	500	34.5	33	8.8
2000	1000	69	32	8.4
2000	1500	103.5	30	8
2000	2000	138	28	7.6
2000	2500	172.5	27	7.1
2000	3000	207	26	6.9